

# FF ADDRESSL

## What it does:

---

Puts the selected address into the document. There are various formats to choose from.

## Used in template:

---

Template				
@v/test/				
FF ADDRESSL/00: @v/00/				
FF ADDRESSL/01: @v/01/				
FF ADDRESSL/03: @v/03/				
FF ADDRESSL/04: @v/04/				

  

Variables				
Name	Type	Action	Length	Prompt
00	@V/	FF ADDRESSL/00	1	Select the address:
01	@V/	FF ADDRESSL/01	1	x
03	@V/	FF ADDRESSL/03	1	X
04	@V/	FF ADDRESSL/04	1	X
TEST	@V/	FF CMLPTS/00	1	x

## What the user sees:

---

Select the address:

Updates completed successfully

Sel	From Date	Type	Address
<input checked="" type="checkbox"/>	8/14/2018	Home	123 W. Main Street Dresden, TN 38225

Select a link to update information

Laura Ingalls [Add a new address](#)

## Output:

---

```
FF ADDRESSL/00: 123 W. Main Street
Dresden, TN 38225
Cell: 305-793-9953; Emergency: 786-205-2133 Grandmother; Home: 305-756-9321

FF ADDRESSL/01: 123 W. Main Street, Dresden, TN 38225

FF ADDRESSL/03: 123 W. Main Street
Dresden, TN 38225

FF ADDRESSL/04: Home Address:
123 W. Main Street
Dresden, TN 38225
Cell: 305-793-9953; Emergency: 786-205-2133 Grandmother; Home: 305-756-9321
```

### FF ADDRESSL/00 – Formats a selected address - stack, w/phone

---

This function is used to format addresses selected by the user of an identity tied to the form. Only active addresses will be included as will any phone numbers. If you want a protected address to actually be output, the variable must end with a '+'. An entry will look something like:

Street  
City, State Zip Country

Number type: number  
Number type: number

### FF ADDRESSL/01 – Formats selected address - string, no phone

---

This function is used to format addresses selected by the user of an identity tied to the form. Only active addresses will be included, but not phone numbers. If you want a protected address to actually be output, the variable must end with a '+'. An entry will look something like:

Street, City, State Zip Country

### FF ADDRESSL/03 – Formats selected address - stack, no phone

---

This function is used to format addresses selected by the user of an identity tied to the form. Only active addresses will be included but not phone numbers. If you want a protected address to actually be output, the variable must end with a '+'. An entry will look something like:

Street  
City, State Zip Country

### FF ADDRESSL/04 – Formats selected address - stack, w/type/phone

---

This function is used to format addresses selected by the user of an identity tied to the form. Only active addresses will be included as will any phone numbers. If you want a protected address to actually be output, the variable must end with a '+'. An entry will look something like:

Address type: Street  
City, State Zip Country

Address type: Street  
City, State Zip Country

Number type: number  
Number type: number