

FF AUTOSIGN

What it does:

This function puts names and signatures into documents based on entries in the defaults table: [FF AutoSign](#).

Used in template:

Template

```
<table width="100%">
<tr width="100%">
<td width="50%"></td>
<td width="50%">@v/CLERKS/</td>
</tr>

<tr>
<td></td>
<td class="tb">@v/CLERKN/|
Juvenile Court Clerk</td>
</tr>
</table>
```


Variables

| Name | Type | Action | Length | Prompt |
|--------|------|----------------|--------|-----------------------------------|
| CLERKN | @V/ | FF AUTOSIGN/01 | 1 | Auto output name to document |
| CLERKS | @V/ | FF AUTOSIGN/00 | 1 | Auto output signature to document |

What the user sees:

The user doesn't see anything

Output:



Kim Huey
Juvenile Court Clerk

FF AUTOSIGN/00 – Auto output signature to document

This function is used to automatically output a signature for the userid identified within the FF AutoSign Defaults table entry. The user id is identified by the entry with the matching variable name to this variable. If no signature exists, the matching user's name is printed instead.

FF AUTOSIGN/01 – Auto output name to document

This function is used to automatically output a name for the userid identified within the FF AutoSign Defaults table entry. The user id is identified by the entry with the matching variable name to this variable.

FF AUTOSIGN/02 – Auto output signature to document

This function is used to automatically output a signature for the userid identified within the FF AutoSign Defaults table entry. The user id is identified by the entry with the matching variable name (plus a '-' plus the current user's employer unit) to this variable. If no signature exists, the matching user's name is printed instead.

Example:

Template variable name: CLERK

Entry in FF AutoSign

CLERK-02=johndoe

FF AUTOSIGN/03 – Auto output name to document

This function is used to automatically output a name for the userid identified within the FF AutoSign Defaults table entry. The user id is identified by the entry with the matching variable name (plus a '-' plus the current user's employer unit) to this variable.

Example:

Template variable name: CLERK

Entry in FF AutoSign

CLERK-02=johndoe

FF AUTOSIGN/04 – Auto output text to document

This function is used to automatically output text identified within the FF AutoSign Defaults table entry. The text is identified by the entry with the matching variable name (plus a '-' plus the current user's employer unit) to this variable.

Example:

Template variable name: CLERK

Entry in FF AutoSign

CLERK-02=Clerk of Allen Superior Court