

# FF COURT

## What it does:

---

Allows you to use the assigned/home court to put information based on that court into your documents. This is helpful when you have multiple court locations.

## Used in template:

---

### Template


```
@v/select/
```

```
<span class="b">YOU ARE FURTHER NOTIFIED AND COMMANDED</span> to appear before the Judge of the @v/court/, @v/courtadd/ for
```

### Variables

Name	Type	Action	Length	Prompt
COURT	@V/	FF COURT/01	1	Long description of the assigned/home court
COURTADD	@V/	FF COURT/05	1	Address of the assigned/home court
SELECT	@V/	FF CMLNPTS/00	1	x

This is all based off the Assigned/home court of the case.

Case type:\* JT - Termination of Parental Rights ▾  
Access:\*  Normal  Confidential  Sealed E  
 Assigned/home court: 75 - Starke Circuit Court

## What the user sees:

---

The user won't see anything, this is automatic.

## Output:

---

```
YOU ARE FURTHER NOTIFIED AND COMMANDED to appear before the Judge of the Starke Circuit Court, 53 East Washington Street, Knox, IN 46534 - 574-772-9147 for
```

## FF COURT/00 – Court assigned to first case - short desc

---

The purpose of this function is to return the short description of the assigned court of the first case (with an assigned court) tied to the document

## FF COURT/01 – Court assigned to first case - long desc

---

The purpose of this function is to return the long description of the assigned court of the first case (with an assigned court) tied to the document

## FF COURT/02 – Court assigned to first case - court type

---

The purpose of this function is to return the type of assigned court for the first case (with an assigned court) tied to the document. To determine the court type, each court entry must have a corresponding entry in the [DEFAULT table](#) of the generic validation tables. It will return the short description of the DEFAULTS entry.

Code	Short description	Long description
<a href="#">Add a new entry</a>		
<a href="#">01</a>	<a href="#">01C</a>	<a href="#">Adams Circuit Court</a>
<a href="#">02</a>	<a href="#">02D</a>	<a href="#">Allen Superior Court</a>
<a href="#">75</a>	<a href="#">75C</a>	<a href="#">Starke Circuit Court</a>

The Assigned/Home Court code and the Default table code must match.

## FF COURT/03 – Court assigned to first case - judge name

---

The purpose of this function is to return the name of the judge for the first case (with an assigned court) tied to the document. To determine the judge's name, each court entry must have a corresponding entry in the DEFAULT table of the generic validation tables. In the notes of the DEFAULTS entry should be 'judgeID=xxx', where xxx is the user id of the judge.

---

Code: 02

Short description:\*

Long description:\*

Active:\*  Yes  No

Notes:

## **FF COURT/04 – Court assigned to first case - judge signature**

---

The purpose of this function is to return the signature of the judge for the first case (with an assigned court) tied to the document. To determine the judge's signature, each court entry must have a corresponding entry in the DEFAULT table of the generic validation tables. In the notes of the DEFAULTS entry should be 'judgeID=xxx', where xxx is the user id of the judge.

## **FF COURT/05 – Court assigned to first case - address**

---

The purpose of this function is to return the address for the first case (with an assigned court) tied to the document. To determine the address, each court entry must have a corresponding entry in the DEFAULT table of the generic validation tables. The address of the DEFAULTS entry should be the address you want printed.

The default table code must have an address and contact number added.

<b>Addresses</b>
6/23/2016 thru present (Work Address) 53 East Washington Street Knox, IN 46534
<b>Contact numbers</b>
Office: 574-772-9147