

FF DEFAULTS

What it does:

This function points to a defaults table and either prints the short description, long description, or notes of that default table.

Used in template:

Template
<pre>@v/*test/ <table width="100%"> <tr width="100%"> <td width="35%" class="l">STATE OF INDIANA</td> <td width="15%" class="l"></td> <td width="50%" class="l">IN THE @v/court</td> </tr> <tr> <td class="l"></td> <td class="l">) SS:</td> <td class="l"></td> </tr></table> <table width="100%"> <tr width="100%"> <td width="35%" class="l">COUNTY OF @v/county</td> <td width="15%" class="l"></td> <td width="25%" class="l">CAUSE NUMBER:</td> <td width="25%" class="l">@v/cause</td> </tr> </table></pre>

Variables				
<hr/>				
Name	Type	Action	Length	Prompt
*TEST	@V/	FF CMPLNTS/00	1	x
CAUSE	@V/	FF CAUSE/00	1	x
COUNTY	@V/	FF DEFAULTSL/99	1	code=county
COURT	@V/	FF DEFAULTSL/99	1	code=court

Default table:

Code	Short description	Long description
Add a new entry		
COUNTY	02	Allen
COURT	D07	Allen Superior Court

What the user sees:

The user doesn't see anything, this is automatic.

Output:

STATE OF INDIANA)	IN THE ALLEN SUPERIOR COURT
COUNTY OF ALLEN) SS:	CAUSE NUMBER:
)	02D07-1703-JD-000255

There are many FF DEFAULTS templates and default tables that can be set up.

FF DEFAULTSL/99 –Formats your entry from defaults - long

This function formats a value in the defaults table. You can specify the value by placing 'code=????' in the prompt, where ???? is the default code to be displayed.

FF DEFAULTSS/99 –Formats your entry from defaults - short

This function formats a value in the defaults table. You can specify the value by placing 'code=????' in the prompt, where ???? is the default code to be displayed.

FF DEFAULTSN/99 –Formats your entry from defaults - notes

This function formats a value in the defaults table. You can specify the value by placing 'code=????' in the prompt, where ???? is the default code to be displayed.