

# FF JUDGE

## What it does:

---

Formats the judge or magistrate's signature, puts %% in the judge area so it goes to the approval list, and formats the judge or magistrate's name.

## Used in template:

---

Template				
@v/pseq/				
FF JUDGE/00: @v/00/				
FF JUDGE/01: @v/01/				
FF JUDGE/02: @v/02/				
FF JUDGE/03: @v/03/				
FF JUDGE/04: @v/04/				
FF JUDGE/05: @v/05/				
FF JUDGE/06: @v/06/				
Variables				
Name	Type	Action	Length	Prompt
00	@V/	FF JUDGE/00	1	x
01	@V/	FF JUDGE/01	1	X
02	@V/	FF JUDGE/02	1	X
03	@V/	FF JUDGE/03	1	X
04	@V/	FF JUDGE/04	1	X
05	@V/	FF JUDGE/05	1	x
06	@V/	FF JUDGE/06	1	x
PSEQ	@V/	FF PSNSEQ/00	1	Enter the Judge UserID:

## What the user sees:

---



Enter the Judge UserID:

Update  Cancel  Refresh

Lookup

## Output:

---

```
FF JUDGE/00: 
FF JUDGE/01:
FF JUDGE/02: 
FF JUDGE/03: %%%
FF JUDGE/04: James H. Bradberry
FF JUDGE/05: James H. Bradberry
FF JUDGE/06:
```

### **FF JUDGE/00 –Format current judge's signature line**

---

Formats the judge's signature line. The person identified by the GAWParms judgePersonID (or defaultJudgeID if judgePersonID = 0) is used. These can be set using the proper FF PSNSEQ function. If the person is authorized to approve forms, either the person's signature (if we have it on file), the name specified in the ApprovalNames table, or the person's name will be output (in that order of precedence); otherwise, %%% will be output.

### **FF JUDGE/01 –Format current magistrate's signature line**

---

Formats the magistrate's signature line. The person identified by the GAWParms judgePersonID (or defaultJudgeID if judgePersonID = 0) is used. These can be set using the proper FF PSNSEQ function. If the person is authorized to approve forms, spaces will be output; otherwise, either the person's signature or name will be output (in that order of precedence).

### **FF JUDGE/02 –Format current judge/magistrate signature line**

---

Formats the judge's signature line. The person identified by the GAWParms judgePersonID (or defaultJudgeID if judgePersonID = 0) is used. These can be set using the proper FF PSNSEQ function. The person's signature (if we have it on file), either the name specified in the ApprovalNames table (if the person is authorized to approve forms), or the person's name will be output (in that order of precedence).

### **FF JUDGE/03 –Format judge's signature line as %%%**

---

## **FF JUDGE/04 –Format current judge/magistrate name**

---

Formats the name of the name of the person identified by the GAWParms judgePersonID (or defaultJudgeID if judgePersonID = 0) is used. These can be set using the proper FF PSNSEQ function. The either the name specified in the ApprovalNames table (if the person is authorized to approve forms) or the person's name will be output (in that order of precedence).

## **FF JUDGE/05 –Format current judge's name**

---

Formats the judge's name. The person identified by the GAWParms judgePersonID (or defaultJudgeID if judgePersonID = 0) is used. These can be set using the proper FF PSNSEQ function. If the person is authorized to approve forms, either the name specified in the ApprovalNames table or the person's name will be output (in that order of precedence); otherwise, spaces will be output.

## **FF JUDGE/06 –Format current magistrate's name**

---

Formats the magistrate's name. The person identified by the GAWParms judgePersonID (or defaultJudgeID if judgePersonID = 0) is used. These can be set using the proper FF PSNSEQ function. If the person is authorized to approve forms, spaces will be output; otherwise, the person's name will be output.