

Rule GAW093 – Event to Contact

Apply when: [Events database file](#)
Subtask: [u](#)
Standard GAWDBObject subtasks:
['C'](#) - on object creation
['R'](#) - before referential integrity
['i'/'I'](#) - before/after insert
['u'/'U'](#) - before/after update
['d'/'D'](#) - before/after delete
Sequence: [25](#) (Controls the order in which rules will be applied for a given subtask)
Java class:*

Creates a contact when an event is completed. Copies the event note to the contact note. You also have the option as to whether you want to do this for court events. It is intended to be used BEFORE UPDATE of the EVENTS database file.

The contact person and contact type are determined by the settings in the 'RULEPARMS' entry of the 'DEFAULTS' table.

Valid properties are:

EventToContact.includeCourt=<yes/no>

EventToContact.default.contactType=<contact type>

EventToContact.default.contactPerson=<contact person>

EventToContact.n=<event type>

EventToContact.n.contactType=<contact type>

EventToContact.n.contactPerson=<contact person>

where

event type is the type of event that is being updated.

contact type is the type of contact that occurred.

contact person is the person who was contacted.

n must start at 1 and increment by 1 for each entry specified.

NOTE: The rule will first look for an event type that matches the passed event type to determine the contact type and contact person. If it can't find one, it will use the default contact type and default contact person.

Rule Setup:

Apply when	Sub-task	Seq	JAVA class
Events	u	25	equest.rules.EventToContact

Rule Parms:

EventToContact.1=pi

EventToContact.1.contactType=pi

EventToContact.1.contactPerson=j

EventToContact.2=pml
EventToContact.2.contactType=pm
EventToContact.2.contactPerson=j