

Rule GAW124 – Protect Contact

Apply when:* CONTACTS - Contacts database file

Subtask:* C

Standard GAWDBObject subtasks:
'C' - on object creation
'R' - before referential integrity
'i'/'I' - before/after insert
'u'/'U' - before/after update
'd'/'D' - before/after delete

Sequence: 4 (Controls the order in which rules will be applied for a given subtask)

Java class:* GAW124 - equest.rules.ProtectContact

This is meant to protect specific contact notes from being seen by people who would otherwise be authorized to it. Therefore, it is best used on creation of the Contacts object. It could also be used before insert to prevent the user from creating an entry too.

The contacts to be protected are determined by the settings in the 'RULEPARMS' entry of the 'DEFAULTS' table.

Valid properties are:

ProtectContact.type.n=<contact type>

ProtectContact.type.n.authorized.m=<group id>

ProtectContact.how.n=<contact how>

ProtectContact.how.n.authorized.m=<group id>

where

<contact type> is the contact type to be protected.

<contact how> is the contact method to be protected.

<group id> is the user group that is authorized.

n must start at 1 (for both type and how) and increment by 1 for each entry specified.

m must start at 1 and increment by 1 for each entry specified - it starts over for each 'n'.

Rule Setup:

Apply when	Sub-task	Seq	JAVA class
Contacts	C	4	equest.rules.ProtectContact
Contacts	i	4	equest.rules.ProtectContact

Rule Parms:

ProtectContact.type.1=