

Rule GAW129 – Secure by Open Case

Apply when:*

Subtask:*

Standard GAWDBObject subtasks:
'C' - on object creation
'R' - before referential integrity
'i'/'I' - before/after insert
'u'/'U' - before/after update
'd'/'D' - before/after delete

Sequence: (Controls the order in which rules will be applied for a given subtask)

Java class:*

Secures a record by checking for open case.
This is meant to protect a descendant of the IDENTITY database object.
It must be used on the 'On Creation' of the database object.

Most groups only have access to the record if the person has an OPEN case of a type the user is authorized to.
The groups with access regardless of case type authority are determined by the settings in the 'RULEPARMS' entry of the 'DEFAULTS' table.

Valid properties are:

SecureByOpenCase.n=<group id>
group id is a user group that has unrestricted access
n must start at 1 and increment by 1 for each entry specified.

Rule Setup:

Apply the rule to any database you don't want people to see if there are no open cases.

Apply when	Sub-task	Seq	JAVA class
SubstanceRpts	C	5	equest.rules.SecureByOpenCase
SubstanceRslts	C	5	equest.rules.SecureByOpenCase
Contacts	C	5	equest.rules.SecureByOpenCase

Rule Parms:

If you want a certain security group to be excluded from this rule and be allowed to view this information add the SecureByOpenCase.1= option.